

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	dormakaba International Holding GmbH
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DOR-20220260-CBA1-EN
Issue date	29.11.2022
Valid to	28.11.2027

EL 301 Series Sliding Door Operator Dormakaba

www.ibu-epd.com | <https://epd-online.com>



ECO PLATFORM

EPD
VERIFIED



General Information

Dormakaba

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-DOR-20220260-CBA1-EN

This declaration is based on the product category rules:

Drive systems for automatic doors and gates, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

29.11.2022

Valid to

28.11.2027



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

EL 301 Series Sliding Door Operator

Owner of the declaration

dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

Declared product / declared unit

1 piece of the product: EL 301 Series - sliding door operator, consisting of the following items:
- EL 301 profiles
- EL 301 drive components, consisting of motor, controller, power supply
- EL 301 belt drive components
- EL 301 accessories battery pack and lock
- EL301 carrier components
- additional mechanical components
- packaging

Scope:

This EPD refers to a specific automatic sliding door operator EL 301 series produced by dormakaba. The production site is located in Hallam, Australia. The material and energy flows were taken into consideration accordingly.

The year of data collection is 2022.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally



Dr.-Ing. Wolfram Trinius,
(Independent verifier)

Product

Product description/Product definition

The dormakaba EL 301 automatic door operator is engineered to control and operate bi-parting and single slide framed and frameless glass sliding doors.

Features

- Total door weight to 300 kg
- Made In Australia
- Integrated uninterruptible power supply (UPS) system
- Smart lock technology

For the placing on the market the following legal provisions apply:

- Australian Standard AS5007
- Endurance testing clause 4.4.1.1. and 4.4.2 by NATA accredited facility.
- 2011/65/EU ROHS3 Directive

Application

The dormakaba EL 301 automatic door operator is a proven performer in airports, shopping centres, supermarkets, hotels, hospitals, financial institutions, sports stadiums and many other commercial sites.

The following parameter are applicable for single and double-leaf doors:

Single-panel sliding door

- Maximum door width: 3000 mm
- Maximum door weight: 300 kg

Double leaf sliding door

- Maximum door width: 1500 mm
- Maximum door weight: 150 kg

Technical Data

The technical data of the EL 301 are as follows:

Constructional data

Name	Value	Unit
Height	240	mm
Installation depth	152	mm
Opening speed maximum	50	cm/s
Closing speed maximum	40	cm/s
Hold open time maximum	60	s
Supply voltage, frequency maximum	60	Hz
Power consumption	175	W
Class of protection	20	IP

Product in accordance with:

- Australian Standard AS5007

LCA: Calculation rules

Declared Unit

The declared unit is 1 piece of the product: EL 301 Series Sliding Door Operator

Declared unit

Name	Value	Unit
Declared unit	1	pce.
Mass (total system) (excl. packaging)	73,14	kg

Delivery status:

The declared EL301 series sliding door operator includes the profiles, drive, belt drive, carrier, battery pack and lock, mechanical components and packaging with a weight of 73,14 kg.

Components	Absolute	Percentage
Average EL 301 Operator	71,71 kg	98,05%
Average Packaging	1,43 kg	1,95%
Total	73,14 kg	100%

Base materials/Ancillary materials

The EL 301 automatic sliding door operator comprises the following components including packaging:

Components	Percentage
Aluminium elements	57,60%
Steel elements	19,00%
Zinc elements	0,35%
Plastic elements	2,05%
Electronic elements	13,13%
Batteries	5,93%
Paper	1,94%
Total	100,00%

The product contains partial articles which contain substances listed in the Candidate List of REACH

Regulation 1907/2006/EC (date: 10.06.2022) exceeding 0.1 percentage by mass: yes

- Lead (Pb): 7439-92-1 (CAS-No) is used in the brass alloy. The concentration of lead in the alloy does not exceed 4%(by mass).
- The drive system is battery-powered (lead accumulator).

Reference service life

The life cycle of the EL 301 series is about 10 years, depending on the application and frequency of use. Regular maintenance is advised to ensure the life expectancy of 10 years. For repairs or renewals, suitable spare parts are available. The EL 301 is tested and certified to 1,000,000 cycles according to AS 5007 NATA accredited.

System boundary

The type of EPD is: cradle-to-gate with options, modules C1–C4, and module D (A1–A3 + C + D and additional modules: A4 + A5 + B6)

Production - Module A1-A3

The product stage includes:

— A1, raw material extraction, processing and mechanical treatments, processing of secondary material input (e.g. recycling processes), — A2, transport to the manufacturer,

— A3, manufacturing and assembly including provision of all materials, products and energy, as well as waste processing up to the end-of waste state.

Construction stage - Modules A4-A5

The construction process stage includes:

- A4, transport to the building site;
- A5, installation into the building;

including provision of all materials, products and energy, as well as waste processing up to the end-of waste state or disposal of final residues during the construction process stage.

Use stage - Module B6

The use stage related to the operation of the building includes:

- B6, operational energy use

End-of-life stage– Modules C1-C4 and D

The end-of-life stage includes:

- C1, de-construction, demolition;
- C2, transport to waste processing;
- C3, waste processing for reuse, recovery and/or recycling;

— C4, disposal; including provision and all transport, provision of all materials, products and related energy and water use.

Module D (Benefits and loads beyond the system boundary) includes:

- D, recycling potentials, expressed as net impacts and benefits.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Australia

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Background database: *GaBi*, SP40.

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

Information on describing the Biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic carbon content in product	0.18	kg C
Biogenic carbon content in accompanying packaging	0.52	kg C

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

The following technical scenario information is required for the declared modules

Transport from the gate to the site (A4)

Name	Value	Unit
Litres of fuel (per 1 kg)	0.00276	l/100km
Capacity utilisation (including empty runs)	55	%
Transport distance via medium truck	100	km

Transport distance is declared for a distance of 100km by truck in order to allow scaling to a specific point of installation.

Installation into the building (A5)

Name	Value	Unit
Waste packaging (paper and plastic)	1.42	kg

Reference service life

Name	Value	Unit
Life Span according to the manufacturer	10	a

Operational energy use (B6)

The use stage is declared for 10 years

Name	Value	Unit
Electricity consumption for 1 year	93.84	kWh
Days per year in use	365	days
On mode per day	1	h
Idle mode per day	7	h
Off mode per day	16	h
On mode power	67,2	W
Idle mode power	7,7	W
Off mode power	8,5	W

End of life (C1-C4)

Name	Value	Unit
Recycling	67.9	kg
Energy recovery	1.27	kg
Landfilling	2.58	kg
Transport to waste management	50	km

The product is disassembled in a recycling process. Material recycling is then assumed for the metals, electronics and electromechanics. The plastic components are assumed to be incinerated with energy recovery. Minor proportions of residues arising from the recycling process are landfilled. Region for the End of Life is: Global.

Reuse, recovery and/or recycling potentials (D), relevant scenario information

The collection rate is 100 %.

LCA: Results

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	X	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 piece EL 301 Sliding Door Operator

Parameter	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	5.31E+02	6.4E-01	2.02E+00	9.42E+02	0	3.11E-01	4.3E+00	1.31E-01	-2.78E+02
GWP-fossil	kg CO ₂ eq	5.33E+02	6.11E-01	6.3E-02	9.41E+02	0	2.98E-01	3.23E+00	1.3E-01	-2.77E+02
GWP-biogenic	kg CO ₂ eq	-2.7E+00	2.8E-02	1.96E+00	8.46E-01	0	1.4E-02	1.07E+00	4.44E-04	-8.52E-01
GWP-luluc	kg CO ₂ eq	3.85E-01	1.46E-05	3.38E-05	2.25E-01	0	7.08E-06	1.89E-04	3.74E-04	-4.1E-02
ODP	kg CFC11 eq	3.74E-09	6.46E-17	3.68E-16	4.3E-12	0	3.14E-17	1.71E-15	4.82E-16	-2.07E-09
AP	mol H ⁺ eq	2.72E+00	6.12E-04	5.65E-04	4.52E+00	0	2.98E-04	6.91E-04	9.33E-04	-1.22E+00
EP-freshwater	kg P eq	7.18E-04	1.31E-07	7.18E-08	4.38E-04	0	6.37E-08	2.72E-07	2.23E-07	-1.39E-04
EP-marine	kg N eq	3.68E-01	1.95E-04	2.04E-04	9.67E-01	0	9.48E-05	1.6E-04	2.4E-04	-1.46E-01
EP-terrestrial	mol N eq	4.01E+00	2E-03	3E-03	1.06E+01	0	1E-03	3E-03	3E-03	-1.58E+00
POCP	kg NMVOC eq	1.15E+00	5.51E-04	5.4E-04	2.69E+00	0	2.68E-04	4.44E-04	7.27E-04	-4.71E-01
ADPE	kg Sb eq	2.35E-02	1.83E-08	5.8E-09	6.31E-05	0	8.93E-09	2.37E-08	1.17E-08	-1.2E-02
ADPF	MJ	6.77E+03	8.67E+00	6.4E-01	1.04E+04	0	4.22E+00	1.65E+00	1.71E+00	-3.88E+03
WDP	m ³ world eq deprived	8.11E+01	1E-03	2.5E-01	3.57E+02	0	5.83E-04	4.28E-01	1.4E-02	-1.42E+01

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential)

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 piece EL 301 Sliding Door Operator

Parameter	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
PERE	MJ	2.4E+03	2.7E-02	1.71E+01	1.59E+03	0	1.3E-02	1.3E+01	2.24E-01	-1.76E+03
PERM	MJ	2.96E+01	0	-1.7E+01	0	0	0	-1.26E+01	0	0
PERT	MJ	2.43E+03	2.7E-02	1.17E-01	1.59E+03	0	1.3E-02	4.18E-01	2.24E-01	-1.76E+03
PENRE	MJ	6.74E+03	8.68E+00	8.55E-01	1.04E+04	0	4.22E+00	3.78E+01	1.71E+00	-3.88E+03
PENRM	MJ	3.63E+01	0	-2.15E-01	0	0	0	-3.61E+01	0	0
PENRT	MJ	6.78E+03	8.68E+00	6.4E-01	1.04E+04	0	4.22E+00	1.65E+00	1.71E+00	-3.88E+03
SM	kg	4.53E+00	0	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0	0
FW	m ³	6.03E+00	4.9E-05	6E-03	5.01E+00	0	2.39E-05	1E-02	4.3E-04	-3.16E+00

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 piece EL 301 Sliding Door Operator

Parameter	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
HWD	kg	1.51E-05	8.42E-10	9.57E-10	1.69E-06	0	4.1E-10	5.8E-09	2.6E-08	-2.13E-05
NHWD	kg	1.15E+02	8.87E-04	6.4E-02	2.69E+00	0	4.32E-04	3.4E-01	8.58E+00	-6.9E+01
RWD	kg	3.61E-01	9.32E-06	3.35E-05	2E-03	0	4.53E-06	6.46E-05	1.94E-05	-4.2E-01
CRU	kg	0	0	0	0	0	0	0	0	0
MFR	kg	0	0	0	0	0	0	6.11E+01	0	0
MER	kg	0	0	0	0	0	0	0	0	0
EEE	MJ	0	0	3.06E+00	0	0	0	0	0	0
EET	MJ	0	0	5.56E+00	0	0	0	0	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:

1 piece EL 301 Sliding Door Operator

Parameter	Unit	A1-A3	A4	A5	B6	C1	C2	C3	C4	D
PM	Disease incidence	2.89E-05	3.22E-09	3.14E-09	4.6E-05	0	1.57E-09	7.97E-09	1.16E-08	-1.78E-05
IR	kBq U235 eq	6.81E+01	1E-03	5E-03	2.53E-01	0	6.48E-04	6E-03	2E-03	-8.45E+01
ETP-fw	CTUe	2.45E+03	6.15E+00	3.03E-01	1.43E+03	0	2.99E+00	6.31E-01	9.75E-01	-1.41E+03
HTP-c	CTUh	2.95E-07	1.16E-10	1.61E-11	8.4E-08	0	5.63E-11	5.5E-11	1.45E-10	-6.1E-08
HTP-nc	CTUh	7.09E-06	4.94E-09	7.09E-10	3.09E-06	0	2.41E-09	5.12E-09	1.59E-08	-1.92E-06
SQP	SQP	1.12E+03	2.2E-02	1.7E-01	9.75E+02	0	1.1E-02	4.92E-01	3.56E-01	-1.19E+02

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator IRP

This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators ADPE, ADPF, WDP, ETP-fw, HTP-c, HTP-nc, SQP

The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

References

Standards

AS 5007

AS 5007-2007 Powered doors for pedestrian access and egress

ISO 14025

DIN EN ISO 14025:201110, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

Further References

2011/65/EU ROHS3 Directive

Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment

IBU 2021

General Instructions for the EPD programme of Institut Bauen und Umwelt e.V.

Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021. www.ibu-epd.com

GaBi ts software

Sphera Solutions GmbH Gabi Software System and Database for Life Cycle Engineering 1992-2020 Version 10.0.0.71

University of Stuttgart Leinfelden-Echterdingen

GaBi ts documentation

GaBi life cycle inventory data documentation (<https://www.gabisoftware.com/support/gabi/gabidatabase-2020-lci-documentation/>).

LCA-tool dormakaba

LCA tool, ENS (drive system) LCA tool no.: IBU-DOR-202108-LT1-EN Developed by Sphera Solutions GmbH.

PCR Part A

PCR – Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Re-port according to EN 15804+A2:2019, Version 1.0, Institut Bauen und Umwelt e.V., www.ibu-epd.com.

PCR Part B

PCR – Part B: Requirements on the EPD for Building Hardware product, version 1.2, Institut Bauen und Umwelt e.V., www.ibu-epd.com, 2020.



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

+49 711 341817-0
info@sphera.com
www.sphera.com



Owner of the Declaration

dormakaba International Holding GmbH
DORMA Platz 1
58256 Ennepetal
Germany

+49 2333 793-0
info.de@dormakaba.com
www.dormakaba.com