HAHN Lamellen		Louvre window S9				
	status:	enquiry	order			
	project number:		purchase order:			
project manager:			phone number:			
desired delivery date:			date:		outside	inside
project					out	<u> </u>
delivery address						
contact person						
on site:		01 02 03				
	no.:	01	02	00		
frame dimensions	width:					
	(mm) height:					
	(mm)	T time 4	D tune 1	To turn 1		
din	type of frame:	type 1 type 2	☐ type 1 ☐ type 2	☐ type 1 ☐ type 2		
frame		type 3 thickness:mm	type 3 thickness: mm	type 3 thickness: mm		ŧ
		(see detail glazingprofile)	(see detail glazingprofile)	(see detail glazingprofile)		neig
	no. of blades:					frame dimensions height
/be	glass thickness:	8mm 10mm	8mm 10mm	8mm 10mm		
blade panel type		☐ 12mm	12mm	☐ 12mm		me d
e ba	type of glass:	toughened glass laminated glass	toughened glass laminated glass	toughened glass laminated glass		fra
blad		idifiliated glass	iammatea glass			
	finish:	powder coated natural anodised	powder coated natural anodised	powder coated natural anodised		
finish	colour supplier	I llaturar arrouised	I llatural allouised	I Ilaturai anodised		
=	& RAL colour:					
controls	type of		manual	manual		
	control:	electricV pneumatic	electricV pneumatic	electricV pneumatic		
	description:	-				
	cable length:	m	m	m		
	(standard = 2,5m) cable exit:					
	(LAH 65 only)	bottom side through frame	bottom side through frame	bottom side through frame		
	control	position A (right side)	position A (right side)	position A (right side)		
	position:	position B (left side) height mm	position B (left side) height mm	position B (left side) height mm	Frame	
	fixing brackets / special adaptor:				type 1	
smoke vents		yes	yes	☐ yes		46.8
CE- certified: no no no						
Frame TIMET						
(A) innen					type 2	
	Frame Figure 1 The second seco					
1	type 1 \$\frac{4}{5}\$					4 8
	51.5					
Elementaußenmaß Breite					20 2 6	
Frame type 2 Frame type 3				Frame		
					type 3	
	8		20.25			
18 51.5				i		
20,25						20,25 40
June 2022 / Subject to change without notice						