UNSER LIFTPORTFOLIO

Gerüstet für jeden Einsatz

Modell	MB750 micro A	MB750 micro B	MB850 micro	MB850 duo	MB 1100, 1400, 1700	MB1000	MB1300	MB Quattro 1100, 1400, 1700	Atlas 3000, 2700, 2400, 2100
Ausstieg: Durchfahrt	●	●	●	●	●	●	●	●	●
Ausstieg: Über-Eck		●	●	●	●			●	●
Ausstieg/Zufahrt auf bis zu 3 Seiten			●	●	●			●	
Förderhöhe ohne Grube	750 mm	750 mm	910 mm	910 mm	1.160, 1.490, 1.790 mm	1.000 mm	1.280 mm	1.190, 1.490, 1.790 mm	2.760–3.060, 2.460–2.750, 2.160–2.450, 1.860–2.150 mm
Förderhöhe bei Einbau in Grube	690 mm	690 mm	850 mm	850 mm	1.100, 1.400, 1.700 mm	945 mm	1.210 mm	1.100, 1.400, 1.700 mm	2.700–3.00, 2.400–2.690, 2.100–2.390, 1.800–2.090 mm
Aufbauhöhe/Grubentiefe	60 mm	60 mm	60 mm	60 mm	60, 90, 90 mm	55 mm	70 mm	90 mm	60 mm
Durchfahrtbreite	720 mm	720 mm	750 mm	900 mm	900 mm	830 mm	900 mm	1.100 mm	900 mm
Breite gesamt	950 mm	1.010 mm	1.100 mm	1.250 mm	1.280 mm	1.190 mm	1.310 mm	1.500 mm	1.245 mm
Länge gesamt	1.330 mm	1.330 mm	1.430 mm	1.430 mm	1.630 mm	1.650 mm	2.000 mm	1.870 mm	1.790 mm
Tragkraft	350 kg	350 kg	300 kg	300 kg	300 kg	300 kg	260 kg	500 kg	385 kg
Hubgeschwindigkeit ca.	1,25 cm/s	1,25 cm/s	2,0 cm/s	2,0 cm/s	2,0 cm/s	1,5 cm/s	1,5 cm/s	2,0 cm/s	bis 1,5 cm/s
Temperaturen	-25 °C bis +40 °C	-25 °C bis +40 °C	-25 °C bis +40 °C	-25 °C bis +40 °C	-25 °C bis +40 °C	-25 °C bis +40 °C	-25 °C bis +40 °C	-25 °C bis +40 °C	-10 °C bis +40 °C
Stromanschluss	230V / 16A	230V / 16A	230V / 16A	230 V / 16A	230V / 16A	230V / 16A	230V / 16A	230V / 16 A	230V / 16 A
Auffahrrahmpen Art	mechanisch	mechanisch	Automatische Klapprampe	Automatische Klapprampe	Automatische Klapprampe	mechanisch	mechanisch	Automatische Klapprampe	integriert in Plattform
OPTIONAL									
Sicherheitsbügel für obere Haltestelle			●	●	●	●	●	●	
Einflügelige Tür für obere Haltestelle	●	●	●	●	●	●	●	●	
Autom. Türöffner für einflügelige Tür obere Haltestelle	●	●	●	●	●	●	●	●	
Autom. Doppelflügel-Tür inkl. Schleife an obere Haltestelle					●				Standard
Schranke als Absicherung untere Haltestelle					●	●	●	●	
Mitfahrende autom. Doppelflügel-Tür auf Plattform untere Haltestelle					●				Standard
Ansteuerung von bauseitigen Türen	●	●	●	●	●	●	●	●	●
Geländer	●	●	●	●	●	Standard	Standard	●	Standard
Handbedienteil Spiralkabel	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Funk- & Smartphone-Steuerung	●	●	●	●	●	●	●	●	●
BarriereFreifahrt Zuganssystem	●	●	●	●	●	●	●	●	●
Bedientableau mit Sensortastern (verschlüsselbar)	●	●	●	●	●	●	●	●	●
Ruftaster mit Sensortastern (verschlüsselbar)	●	●	●	●	●	●	●	●	●
Unterbrechungsfreie Stromversorgung extern	●	●	●	●	●	●	●	●	●
Akkugestütztes Notablass-System intern			●	●	●	●	●	●	
Notruf-Telefon (GSM oder Kabel)	●	●	●	●	●	●	●	●	●
Notklingel	●	●	●	●	●	●	●	●	●