

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-003.0-06

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Factory made mineral wool (MW) products for thermal insulation of building
equipment and industrial installations**
(details cf. annex)

Placed on the market under the name or trade mark of

SAINT-GOBAIN ISOVER G+H AG

Bürgermeister-Grünzweig-Str. 1

67059 Ludwigshafen

Germany

and produced in the manufacturing plant

Speyer

Industriestraße 125

67346 Speyer

Germany

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 14303:2009+A1:2013

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 17.02.2014 and will remain valid (but no longer than 02.12.2025) as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Gräfelfing, 02.12.2024



A publication of extracts or a referring to the Certificate of Constancy of Performance and its annex requires the prior written approval of FIW München. Certification body accredited by DAkkS according to DIN EN ISO/IEC 17065:2013. The accreditation is only valid for the scope of accreditation listed in the annex to the certificate D-ZE-14116-01-00.

Factory:

Speyer, Industriestraße 125, 67346 Speyer, Germany

Construction product(s):

Factory made mineral wool (MW) products for thermal insulation of building equipment and industrial installations according to EN 14303:2009+A1:2013

Intended use:

Thermal insulation products for building equipment and industrial installations

Level(s) or class(es) reaction to fire:

for uses subject to regulations on reaction to fire A1. Products for which a clearly identifiable stage in the production process results in an improvement in the reaction to fire classification by limiting of organic material.

No.	Form	Name	Product Description	Reaction to fire EN 13501-1				
				Nominal density	Classification	Range	Fire Group	Classification report
1	Slab	Rohling 5 kPa - Stadur	Roll made of non-combustible mineral wool covered with reinforced aluminum foil	14 kg/m ³	A1	Max. organic content: 6,4 %	3	KB-Hoch -130032
2	Roll	FT	Roll made of non-combustible mineral wool	15 kg/m ³ - 22 kg/m ³	A1	Max. organic content: 6,4 %	3	KB-Hoch -130032
3	Roll	FE	Roll made of non-combustible mineral wool	19 kg/m ³	A1	Max. organic content: 6,4 %	3	KB-Hoch -130032
4	Roll	Metac UF-035 / si	Roll made of non-combustible mineral wool	19 kg/m ³	A1	Max. organic content: 6,4 %	3	KB-Hoch -130032
5	Slab	Rohling 10 kPa - Stadur	Roll made of non-combustible mineral wool	19 kg/m ³	A1	Max. organic content: 6,4 %	3	KB-Hoch -130032
6	Slab	P4	Slab made of non-combustible mineral wool	23 kg/m ³	A1	Max. organic content: 6,4 %	3	KB-Hoch -130032
7	Roll	FK	Roll made of non-combustible mineral wool	24 kg/m ³	A1	Max. organic content: 6,4 %	3	KB-Hoch -130032
8	Roll	TECH ROLL 2.0	Roll made of non-combustible mineral wool	24 kg/m ³	A1	Max. organic content: 6,4 %	3	KB-Hoch -130032

No.	Product			Reaction to fire EN 13501-1				
	Form	Name	Description	Nominal density	Classification	Range	Fire Group	Classification report
9	Roll	FK/AGF	Roll made of non-combustible mineral wool covered with reinforced aluminium foil	24 kg/m ³	A1	Max. organic content: 4,8 %	6	KB-Hoch-141181
10	Roll	TECH ROLL 2.0 Alu1	Roll made of non-combustible mineral wool covered with reinforced aluminium foil	24 kg/m ³	A1	Max. organic content: 4,8 %	6	KB-Hoch-141181
11	Roll	FK/G-H	Roll made of non-combustible mineral wool covered with side glass tissue	24 kg/m ³	A1	Max organic content: 5,4 % or 1,6 kg/m ³	11	KB-Hoch-190098
12	Roll	TECH ROLL 2.0 V1	Roll made of non-combustible mineral wool covered with side glass tissue	24 kg/m ³	A1	Max organic content: 5,4 % or 1,6 kg/m ³	11	KB-Hoch-190098
13	Lamella mat	CLIMCOVER Lamella Mat	Lamella mat made of non-combustible mineral wool covered with rein-forced aluminium foil	27 kg/m ³	A1	Max. organic content: 4,8 %	6	KB-Hoch-141181
14	Lamella mat	ML 3	Lamella mat made of non-combustible mineral wool covered with rein-forced aluminium foil	27 kg/m ³	A1	Max. organic content: 4,8 %	6	KB-Hoch-141181
15	Slab	PF 28	Slab made of non-combustible mineral wool	28-36 kg/m ³	A1	Max. Organic content: 5,4 %	10	KB-Hoch-170365
16	Roll	FI	Roll made of non-combustible mineral wool	30 kg/m ³	A1	Max. Organic content: 5,4 %	10	KB-Hoch-170365
17	Slab	P 4/V	Roll made of non-combustible mineral wool covered with side glass tissue	48 kg/m ³	A1	Max organic content: 5,4 % or 1,6 kg/m ³	11	KB-Hoch-190098

Product		Reaction to fire EN 13501-1						
No.	Form	Name	Description	Nominal density	Classification	Range	Fire Group	Classification report
18	Lamella mat	ML-DT	Lamella mat made of non-combustible mineral wool covered with rein-forced aluminum foil	48 kg/m ³	A1	Max. Organic content: 5,4 %	10	KB-Hoch-170365
19	Lamella mat	Tech Lamella Mat 2.0	Lamella mat made of non-combustible mineral wool covered with rein-forced aluminum foil	48 kg/m ³	A1	Max. Organic content: 5,4 %	10	KB-Hoch-170365

Detail information about the insulation products are given in the classification reports
 Gräfelfing 02.12.2024



Alberti