

## DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011  
(Construction Products Regulation)

### Nr. DoP-DE-tec 772

- Unique identification code of the product-type:*  
**weber.tec 772**  
**Surface protection product-coating** according to DIN EN 1504-2
- Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*  
Batch/production date/production site/serial No. is printed on packaging or accompanying documents
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*  
Surface protection product - hydrophobic impregnation. Intended uses: ingress protection (1.3), moisture control (2.2), increasing resistivity (8.2)
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*  
Saint-Gobain Weber GmbH  
Schanzenstr. 84  
D-40549 Düsseldorf  
[www.sg-weber.de](http://www.sg-weber.de)
- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*  
not applicable
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*  
System 2+
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:*  
The notified body Kiwa Polymer Institut GmbH, identification number 1119, performed the initial inspection of the manufacturing plant and of factory production control (FPC), performs continuous surveillance, assessment and evaluation of FPC under system 2+ and issued certificate of conformity of the factory production control No. 1119-CPR-1077.
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*  
not applicable

9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
Linear shrinkage	NPD	DIN EN 1504-2:2005-01
Coefficient of thermal expansion	NPD	
Cross cut	≤ GT 2	
Permeability to CO <sub>2</sub>	s <sub>D</sub> > 50 m	
Water vapour permeability	Class I	
Capillary absorption and permeability to water	w < 0,1 kg/m <sup>2</sup> x h <sup>0,5</sup>	
Thermal compatibility	≥ 0,8 N/mm <sup>2</sup>	
Resistance to thermal shock	NPD	
Resistance to severe chemical attack	NPD	
Crack bridging ability	B 2 (-20 °C)	
Adhesive strength	≥ 0,8 N/mm <sup>2</sup>	
Reaction to fire	Class E	
Skid resistance	NPD	
Artificial weathering	No visual defects	
Antistatic behaviour	NPD	
Adhesion on wet concrete	NPD	
Dangerous substances	In accordance with EN 1504-2, 5.3	

NPD (No Performance Determined)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Bruno Reisch, Direktor Technik

Düsseldorf, ..... July 11, 2013 .....  
(Place and date of issue)

..... ppa Reisch .....  
(Signature)

Annex  
Material safety data sheet weber.tec 772