

DECLARATION OF PERFORMANCE

No.: Rigips_Glasroc_X_125_LE_2405

(1) *Unique identification code of the product-type*
Rigips Glasroc X 12.5

(2) *Intended use/es*
**Gypsum boards with fibrous reinforcement for the use in building construction
GM-FH1 (EN 15283-1) 12.5 mm**

(3) *Manufacturer*
**SAINT-GOBAIN RIGIPS GmbH
Schanzenstr. 84
D-40549 Düsseldorf**

(4) *Authorised representative*
N/A

(5) *System/s of AVCP*
**System 3 for reaction to fire
System 4 for all other properties**

(6a) *Harmonised standard*
EN 15283-1:2008+A1:2009

Notified body/ies
**Prüfinstitut für das Brandverhalten von Bauprodukten Dipl.-Ing. (FH) Andreas
Hoch (1508)**

(6b) *European Assessment Document*
N/A

European Technical Assessment
N/A

Technical Assessment Body
N/A

Notified body/ies
N/A

(7) Declared performance/s


Essential characteristics	Performance
Reaction to fire (R2F) (for unprotected installation situations)	A1
Shear strength ($\uparrow\downarrow$) (for stiffening of timber frame outer walls and timber roof constructions)	NPD
Flexural strength (Bending breaking load)	L/II: 538 N - T/L: 210 N
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance (μ)	18.2
Thermal resistance specified as thermal conductivity (λ)	0.25
Impact resistance Airborne sound insulation (R) Acoustic absorption (α)	See system documentation of Saint-Gobain Rigips GmbH or from the local supplier

(8) Appropriate Technical Documentation and/or Specific Technical Documentation
N/A


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Düsseldorf, 10. September 2024



Cordula Gudduschat, Managing Director



Dr. Benjamin Kaplan, Director R&D Isover/Rigips Germany

CE	
SAINT-GOBAIN RIGIPS GmbH Schanzenstr. 84 D-40549 Düsseldorf	
16 Rigips_Glasroc_X_125_LE_2405	
EN 15283-1:2008+A1:2009 Gypsum boards with fibrous reinforcement for the use in building construction GM-FH1 (EN 15283-1) 12.5 mm Notified body/ies: 1508	
Reaction to fire (R2F) (for unprotected installation situations)	A1
Shear strength (↑↓) (for stiffening of timber frame outer walls and timber roof constructions)	NPD
Flexural strength (Bending breaking load)	L/II: 538 N - T/L: 210 N
Water vapour permeability (to control water vapour diffusion) specified as water vapour diffusion resistance (μ)	18.2
Thermal resistance specified as thermal conductivity (λ)	0.25
Impact resistance Airborne sound insulation (R) Acoustic absorption (α)	See system documentation of Saint-Gobain Rigips GmbH or from the local supplier